



Available  
in Brass or  
Acetal

# DualFit™

FITS  
NPT and  
BSPT

**STOP!**  
Now you can use NPT  
fittings on your metric  
machine tools! Put  
that NPT tap away!

These work  
great with TurretJets  
and CapJets!



## PIPE FITTINGS FOR COOLANT NOZZLES

- Fits both NPT and BSPT (metric pipe) threads
- Compact design is ideal for tight spaces
- Allows you to use inch or metric fittings and nozzles
- Acetal version rated to 150 PSI (10 bar) maximum
- Brass version rated to 1500 PSI (100 bar) maximum



DualFit brass adaptor allows PressureMax nozzle to be used in screw-lock socket having BSPT port.

### DIMENSIONS IN INCHES

	Part No.	Thread E	Thread F	Material	"L"	A	D	Dia d	Pkg Qty	Configuration
Close Nipple	DF08505	1/8 NPT/BSPT	1/8 NPT/BSPT	Acetal	.80	.40	.41	.25	5	
	DF08705B	1/8 NPT/BSPT	1/8 NPT/BSPT	Brass	.80	.40	.41	.25	5	
	DF08510	1/4 NPT/BSPT	1/4 NPT/BSPT	Acetal	.88	.44	.53	.31	5	
	DF08710B	1/4 NPT/BSPT	1/4 NPT/BSPT	Brass	.88	.44	.53	.31	5	
	DF08515	3/8 NPT/BSPT	3/8 NPT/BSPT	Acetal	1.00	.50	.66	.44	5	
	DF08715B	3/8 NPT/BSPT	3/8 NPT/BSPT	Brass	1.00	.50	.66	.44	5	
Long Nipple	DF08520	1/8 NPT/BSPT	1/8 NPT/BSPT	Acetal	1.50	.34	.41	.25	5	
	DF08720B	1/8 NPT/BSPT	1/8 NPT/BSPT	Brass	1.50	.34	.41	.25	5	
	DF08525	1/4 NPT/BSPT	1/4 NPT/BSPT	Acetal	1.50	.44	.53	.31	5	
	DF08725B	1/4 NPT/BSPT	1/4 NPT/BSPT	Brass	1.50	.44	.53	.31	5	
	DF08530	3/8 NPT/BSPT	3/8 NPT/BSPT	Acetal	1.50	.50	.66	.44	5	
	DF08730B	3/8 NPT/BSPT	3/8 NPT/BSPT	Brass	1.50	.50	.66	.44	5	
Bushing	DF08835B	M12x1.75	1/8 NPT/BSPT	Brass	.81	.50	.56	.28	5	
	DF08840B	M14x1.0	1/8 NPT/BSPT	Brass	.40	.28	.62	.31	5	
	DF08535	1/4 NPT/BSPT	1/8 NPT/BSPT	Acetal	.65	.44	.56	.31	5	
	DF08735B	1/4 NPT/BSPT	1/8 NPT/BSPT	Brass	.65	.44	.56	.31	5	
	DF08540	3/8 NPT/BSPT	1/4 NPT/BSPT	Acetal	.73	.50	.75	.42	5	
	DF08740B	3/8 NPT/BSPT	1/4 NPT/BSPT	Brass	.73	.50	.75	.42	5	
Adaptor	DF08545	1/8 NPT/BSPT	1/8 NPT/BSPT	Acetal	.78	.40	.46	.25	5	
	DF08745B	1/8 NPT/BSPT	1/8 NPT/BSPT	Brass	.78	.40	.46	.25	5	
	DF08550	1/4 NPT/BSPT	1/4 NPT/BSPT	Acetal	.93	.50	.60	.31	5	
	DF08750B	1/4 NPT/BSPT	1/4 NPT/BSPT	Brass	.93	.50	.60	.31	5	
	DF08555	3/8 NPT/BSPT	3/8 NPT/BSPT	Acetal	1.04	.55	.73	.37	5	
	DF08755B	3/8 NPT/BSPT	3/8 NPT/BSPT	Brass	1.04	.55	.73	.37	5	

Maximum Pressure: Acetal: 150 PSI (10 bar) Brass: 1500 PSI (100 bar)

Maximum Operating Temperature: Acetal: 160°F Brass: 300°F

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE OR OBLIGATION.

Adaptors are great for  
mounting TurretJet and  
PressureMax nozzles in  
counterbored ports

DF08840B  
is perfect for  
JOHNFORN  
Turning  
Centers