



SprayTips



SCREW-IN, BRASS SPRAY TIPS FOR USE IN TAPPED-BALL NOZZLES

- Available in various orifice diameters ■ Ideal for concentrating the coolant stream at the cutting edge
- Angled outlet **SprayTips** enable aiming outside a nozzle's normal range of motion

DIMENSIONS IN INCHES

Type	Part No.	Mounting Thread "E"	Orifice Dia. "d"	Overall Length "L"	Thread Length "A"	"C" Hex	Pkg Qty	Configuration
Straight Outlet	ST16510	M3.5 x .6	.062	.42	.14	3/16	5	
	ST16515	M3.5 x .6	.086	.42	.14	3/16	5	
	ST16520	M4 x .7	.062	.54	.18	3/16	5	
	ST16525	M4 x .7	.086	.54	.18	3/16	5	
	ST16530	M5 x .8	.062	.63	.21	1/4	5	
	ST16535	M5 x .8	.086	.63	.21	1/4	5	
	ST16540	M5 x .8	.117	.63	.21	1/4	5	
	ST16545	M6 x 1.0	.062	.63	.21	1/4	5	
	ST16550	M6 x 1.0	.086	.63	.21	1/4	5	
	ST16555	M6 x 1.0	.117	.63	.21	1/4	5	
	ST16560	M6 x 1.0	.150	.63	.21	1/4	5	
	ST16565	M8 x 1.25	.062	.80	.30	3/8	5	
	ST16570	M8 x 1.25	.086	.80	.30	3/8	5	
	ST16575	M8 x 1.25	.117	.80	.30	3/8	5	
	ST16580	M8 x 1.25	.160	.80	.30	3/8	5	
	ST16585	M8 x 1.25	.220	.80	.30	3/8	5	
	ST16610	1/8NPT/BSPT	.062	.90	.37	1/2	5	
	ST16615	1/8NPT/BSPT	.086	.90	.37	1/2	5	
	ST16620	1/8NPT/BSPT	.117	.90	.37	1/2	5	
	ST16625	1/8NPT/BSPT	.160	.90	.37	1/2	5	
ST16630	1/8NPT/BSPT	.220	.90	.37	1/2	5		
ST16635	1/8NPT/BSPT	.280	.90	.37	1/2	5		
Angled Outlet	ST16650	M3.5 x .6	.062	.32	.14	3/16	5	
	ST16655	M4 x .7	.062	.36	.18	3/16	5	
	ST16660	M5 x .8	.086	.42	.21	1/4	5	
	ST16665	M6 x 1.0	.086	.42	.21	1/4	5	
	ST16670	M6 x 1.0	.117	.42	.21	1/4	5	



SprayTips can be used in a wide variety of nozzles including:
ScrewBolts, JetBolts, BrassBalls, BlackEyes, TurretJets, JetTubes, SweatJets, CapJets and BugEyes.

Material: Brass

Maximum Pressure: 500° psi (33 bar)